




BS88, IEC269 Industrial HRC Fuse Links


ESD

Offset Blade Tags 550V ac and 415V ac

Time-Current Characteristic Curves



Dimensional Data



The ESD range of Fuse Links comply with general purpose gG characteristics and fit into the SAFELOC Fuse Holders and into the CAMLOC Distribution Fuseboard System.

Packaging - 20 per carton

Catalog Number	I ² t (Amp ² Seconds)			Nom. Watts Loss	Rated Voltage	Dimensions (inches/mm)					
	Amp Ratings	Pre-Arcing	Total at 415V			A	B	D	E	F	N
ESD2	2	1.3	4.6	0.9	550 ac	1.43 35.5	.54 13.8	2.65 68.0	.58 15.0	.05 1.2	.14 3.5
ESD4	4	8	27	1.4							
ESD6	6	29	100	1.8							
ESD10	10	120	400	2.1							
ESD16	16	120	470	1.8							
ESD20	20	260	1070	1.8							
ESD25	25	560	2300	2.0							
ESD32	32	710	3000	2.9	415 ac	0.69 17.5	0.84 21.0				
ESD40	40	1500	6000	3.2							
ESD50	50	2700	8700	3.9							
ESD63	63	5000	13,300	4.6							
ESD63M80	63M80	12,700	40,000	3.4							
ESD63M100	63M100	20,700	70,000	2.5							

This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.



Bussmann

Bussmann Division
Cooper (U.K.) Ltd
 Burton-on-the-Wolds
 Leicestershire, LE12 5TH
 United Kingdom
 Tel: (44) (0)1509 88 27 37
 Fax: (44) (0)1509 88 27 86

Head Office
 St. Louis, MO, U.S.A. Tel: (314) 527-3877 Fax: (800) 544-2570 International Fax: (314) 527-1445



Bussmann Information Fax (00 1) 314 527 1450